

Tread design	Tyre size	Ply rating	TT/TL	Section (mm)	Overall diameter (mm)	Static loaded radius (mm)	Rolling circumference (mm)	Lug height	Inflation pressure	Maximum load per tyre	Recommended rim size/type	Max speed (km/h)
PD5	13x5.00 - 6	2	TL	122	320	145	925	3.0	1.4	135	3.50A	15
PD3	14x5.00 - 6	2	TL	135	350	161	1026	4.6	1.4	155	3.50A	15
M40B	15x6.00 - 6	2	TL	155	366	165	1052	4.0	1.0	165	4.50A	15
PD	13x6.00 - 8	2	TL	148	342	157	1001	4.0	1.2	110	5.00	15
PD1	16x6.50 - 8	2	TL	165	406	185	1179	4.6	1.0	190	5.375I	15
PD5	16x6.50 - 8	2	TL	165	406	181	1154	5.0	1.0	190	5.375I	15
M40B	16x6.50 - 8	2	TL	165	406	184	1173	4.6	1.0	190	5.375I	15
PD1	16x6.50 - 8	4	TL	165	406	185	1179	4.6	2.0	285	5.375I	15
M40B	16x6.50 - 8	4	TL	165	411	188	1198	5.0	2.0	285	5.375I	15
PD	18x7.00 - 8	4	TL	170	457	208	1326	5.0	2.0	310	5.50	15
M40B	210/60D8	56 A6	TL	202	406	215	1370	6.0	1.6	225	5.50	30
PD3	18x8.50 - 8	2	TL	213	448	199	1268	8.6	0.7	235	7.00I	15
PD	18x8.50 - 8	4	TL	213	448	199	1268	6.0	1.0	280	7.00I	15
PR	18x8.50 - 8	4	TL	213	445	206	1313	4.5	1.0	280	7.00I	15
SO	18x9.50 - 8	2	TL	223	433	182	1160	-	0.8	305	7.00I	15
PD	18x9.50 - 8	4	TL	222	461	204	1300	5.8	1.4	325	7.00I	30
M40B	20x1000 - 8	2	TL	254	500	216	1377	6.0	0.8	350	8.5JA	15
M40B	20x1000 - 8	4	TL	239	500	216	1377	6.0	1.4	485	7.00I	15
PD1	16x4.50 - 9	2	TT	105	405	193	1230	3.0	1.4	75	3.00D	15
PD	19x8.00 - 10	2	TT	210	485	224	1428	5.6	0.8	215	7.00	15
PD	20x8.00 - 10	4	TT/TL	193	495	224	1428	7.0	1.6	400	6.00I	15
M40B	20x8.00 - 10	4	TL	193	495	223	1421	6.0	1.6	400	6.00I	15
PD1	20.5x8.00 - 10	4	TL	208	526	241	1536	7.0	1.6	410	6.00I	15
PD2	21x11.00 - 10	2	TT/TL	268	528	222	1415	13.0	0.6	355	8.50I	15
FD	6.-12	4	TT	155	564	262	1670	8.4	2.0	270	5JA	30
PD1	22x8.50 - 12	4	TL	216	546	245	1562	8.6	1.6	505	7JA	15
PD	23x8.50 - 12	4	TL	213	578	262	1670	8.6	1.6	505	7JA (7.00I)	15
M40B	23x8.50 - 12	4	TL	213	594	265	1689	6.0	1.6	505	7JA	15
PD1	24x8.50 - 12	4	TL	216	602	278	1772	8.6	1.6	550	7JA	15
M40B	24x8.50 - 12	4	TL	224	614	282	1798	6.0	1.6	550	7JA	15
PD1	23x10.50 - 12	2	TL	264	579	251	1600	7.6	0.7	405	8.5JA	15

Tread design	Tyre size	Ply rating	TT/TL	Section (mm)	Overall diameter (mm)	Static loaded radius (mm)	Rolling circumference (mm)	Lug height	Inflation pressure	Maximum load per tyre	Recommended rim size/type	Max speed (km/h)
M40B	23x10.50 - 12	2	TL	264	579	255	1625	8.0	0.7	405	8.5JA	15
PD1	23x10.50 - 12	4	TL	264	579	261	1664	7.6	1.4	605	8.5JA	15
M40B	23x10.50 - 12	4	TL	241	594	266	1696	8.0	1.4	605	7JA	15
PD1	26x12.00 - 12	4	TL	300	660	284	1810	9.0	1.2	775	9.75I	15
FTA	10.0/80 - 12	6	TT/TL	244	695	311	1982	15	2.3	1040	7JA	15
FD	6.-14	4	TT	155	614	286	1823	8.4	2.0	305	5JA	30
FD	7.-14	4	TT	175	660	304	1938	8.4	1.8	370	5JA	30
PD1	24x8.50 - 14	4	TL	216	602	271	1727	8.6	1.6	550	7JA	15
PD1	25x8.50 - 14	4	TL	216	635	289	1842	8.6	1.6	525	7JA	15
M40B	250/60D14	79 A6	TL	246	656	300	1912	6.0	1.6	437	7JA	30
PD1	27x8.50 - 15	4	TL	214	681	303	1931	8.6	1.6	650	7JA	15
PD	27x8.50 - 15	4	TT/TL	212	681	302	1925	8.6	1.6	650	7JA	15
PD1	29x12.00 - 15	4	TL	297	757	342	2180	9.0	1.4	810	10LB	15
M40B	315/75D15	4	TL	316	853	389	2480	9.0	1.0	615	10LB	30
PD1	31x13.50 - 15	4	TL	348	777	341	2174	9.6	1.4	985	10LB	15
PD1	31x15.50 - 15	4	TL	394	785	353	2250	9.6	1.4	865	13LB	30
PD1	212/80D15	4	TT	215	721	339	2161	8.5	1.6	435	7JA	30
FD	8.-16	4	TT	210	805	371	2365	10	1.6	475	5JA	30
FD	9.5 - 16	4	TT	242	820	377	2403	15	1.4	555	W8	30
FD	9.5 - 16	6	TT	242	820	379	2416	15	2.2	725	W8	30
M40B	315/80D16	4	TL	316	910	415	2645	9.0	1.0	685	10LB	30
PD1	13.6 - 16	4	TT	347	988	449	2862	10	1.0	800	W11	30
FD	13.6 - 16	4	TT	341	982	449	2862	20	1.0	800	W11	30
FD	9.5 - 18	4	TT	242	870	399	2543	15	1.4	600	W8	30
FD	9.5 - 18	6	TT	242	870	402	2562	15	2.0	740	W8	30
PD1	355/80D20	4	TT	353	1076	496	3162	10.0	1.0	825	W11	30
PD1	475/65D20	4	TT	464	1133	505	3219	13.5	0.8	1180	W15L	30
FD	11.2 - 24	4	TT	275	1071	481	3066	16.5	1.2	845	W9	30
FD	13.6 - 28	6	TT	345	1287	585	3729	20	1.6	1430	W11	30